



COMPANIA GENERAL DE LUBRICANTES SA

C/ Comercio, 36 – Polígono Industrial Can Sunyer
08740 SANT ANDREU DE LA BARCA (Barcelona)
Telf: +34 93 6821514 – Fax: +34 93 6820055
e-mail: gro@cogelsa.com

TECHNICAL DATA SHEET

FOAM FILTER SPRAY

GLOBAL RACING OIL FOAM FILTER SPRAY provides superior filtration characteristics to guarantee maximum motor efficiency and protects the internal components against contaminants, both new and old filters.

FOAM FILTER SPRAY protects filters against water, avoids moisture and prevents obstructions, increase filter shelf life and provides efficient sealing. Due to its superior properties, retains dust, sand and dirt. The dark blue pigment allows an easy appreciation of the correct maintenance.

FOAM FILTER SPRAY offers the following properties:

- Protects against water
- Specially designed to protect against dust, sand and dirt
- Quickly penetrates the filter pleats, avoiding dropping.
- Easy to apply

Density	0,90
Viscosity at 40°C	7 cSt
Pour Point	-12°C
Color	Dark blue

According to the exigencies :

Yamaha, Suzuki, Alfer, Mecatecno, Honda, Rieju.

REV: 02/17

Assessment with respect to the elaboration and utilization of “plannings” for the control and conservation of plants and industrial equipment. COMPANIA GENERAL DE LUBRICANTES S.A. is not accountable for the legal actions arised from the inadequate use of the product or products, herein referred to, being, according to our criteria, correct and complying with the quoted DESCRIPTIONS and APPLICATIONS contained herein.

COMPANY CERTIFIED

